



## ► PREMIUM PLUS RANGE

THE PREMIUM PLUS ESPRESSO MACHINE RANGE IS THE LATEST MACHINE RANGE FROM ROCKET ESPRESSO, AND OUR FLAGSHIP MODELS. FEATURES INCLUDE OUR PROVEN THERMO SIPHON SYSTEM, NICKEL PLATED BOILER WITH LEAD FREE BRASS END PLATES FOR INCREASED THERMAL RETENTION.

NEW TO THE PREMIUM PLUS RANGE IS THE FULL COMMERCIALY RATED SIRAI PRESSURE STAT, WHICH HAS A FAR GREATER DEGREE OF ACCURACY OVER THE LIFE TIME OF THE MACHINE. ADDITIONALLY, THE THERMO SIPHON SYSTEM HAS BEEN ENHANCED THROUGH THE USE OF INCREASED DIAMETER COPPER TUBES THAT SUPPLY THE WATER TO THE BREWING GROUP. NOW INCLUDES A WATER RESERVOIR, LOW LEVEL, INDICATION WARNING SYSTEM.



**ROCKET**<sup>®</sup>  
ESPRESSO MILANO

## GIOTTO AND CELLINI TECHNICAL INFORMATION

Bodywork	All stainless steel (AISI 304)
Brewing head	Commercial brewing head. Weight id 4.05 kg (9 lbs)
Pre-infusion	Dual pre-infusion system: mechanical pre-infusion system with progressively working piston and static pre-infusion chamber. This reflects into smooth coffee extraction with optimum aroma, body and “crema”.
Thermosyphon system	Superior layout of thermosyphon system resulting in optimum extraction. Generously dimensioned. 20% higher volume as with comparable machines on the market.
Boiler	Boiler is made of pure copper (Cu. 99.9%) with a lead free, heavy brass end plate to increase the thermal retention and the steam power by approximately 40% versus other boiler systems. Boiler is nickel plated for protection against copper oxidation. Boiler capacity: 1.8 l.
Pressure control switch	Giotto and Cellini now come with a full size commercially rated pressure switch (0,035°C temperature differential tolerance). Optional for some markets.
Stainless steel steam wand	With our patented cool-touch technology: anti-burn (only the nozzle gets hot); easy cleaning as milk doesn't bake on wand; more efficient steam, as heat is not dissipated around the wand. Steam nozzle designed for easy milk foaming with fine texture.
Electronically controlled	Microprocessor controlled automatic level control of boiler and fresh water reservoir, with low water level indication warning system.
Heating	Optimised boiler capacity to thermosyphon system ratio. Results in fast heat up time with 1200 watt element, made from special long life material (5 times longer than normal elements).
Safety Valve	Fully certified commercially rated safety valve.
Fresh Water Capacity	2.9 l
Dimensions (W x D X H)	33 x 42.5 x 35 cm. Weight: 23kg (46.3 lbs) Cellini – 30 cm wide
Additionally	Full size commercial one and two cup filter handles, and baskets. Full training guide and instructions.